

Simplex and Duplex SC-SC/APC SM Fiber Adapters



ADF-102



ADF-103



ADF-104

MODEL	ADF-102	ADF-103	ADF-104
REF.	8243	8292	8291
Connector type	SC-SC	SC-SC	SC-SC
Polishing	APC	APC	APC
Fiber	SM	SM	SM
Format	Simplex With fixing screws	Simplex Without fixing screws	Duplex With fixing screws
Material	Plug	Translucent propylene - PP	
	Flange	Acero inoxidable - SUS304	
	Housing	Polycarbonate - PC	
	Core	Tereflato de polietileno - PET+GF	
	Ferrula	Ceramic - Zirconia ZrO2	
Tensile strength	2.0 ~ 5.9 N		
Insertion loss	≤ 0.25 dB		
Wavelength	1310nm ~ 1550nm ~ 850nm		
Durability	Cycles	> 500 times	
	Loss	< 0.2 dB	
Operating temperature	-40 ... +75 °C		

- Adapters for SC-SC (female-female) APC fibre optic connectors in simplex and duplex format, green zirconia.
- Use in boxes, panels, trays, rosettes and any fibre optic equipment in telecommunication networks, CATV, LAN, broadband, FTTH, etc.
- They incorporate a black and a translucent cap for easy identification by means of a VFL.

MODEL	TA-001
REF.	8290

Fibreboard adapter fixing screws

Bag of 50 pieces

Standard

IEC 60874-14, 60793-2-10 A1a
IEC 793, 794-1 E1 E3, 11801 2nd Ed.
CECC 86115-801, ICEA-596,
Telcordia GR-326, GR-409-CORE
EIA/TIA 604-3A, 568, 455
EN 50173, JIS C5973 F04,
ITU-T G.651, G.652



RoHS
Compliant