

8-way Tap-offs

UDL816

REF. 3366

UDL825

REF. 3368

UDL820

REF. 3367



- Frequency range: 5-2300 MHz.
- Wall fixing, nickle-plated zinc diecast housing (2 screws attached).
- Grounding facilities.
- All ports F female connector.
- DC transit (max +24 V_{DC}, 0.5 A) on the main line.

		UDL-816	UDL-820	UDL-825
Tap loss (± 1 dB)	dB	16	20	25
Through loss	5 – 862 MHz	≤ 4.0	≤ 1.8	≤ 1.8
	950 – 1550 MHz	≤ 4.4	≤ 2.0	≤ 2.0
	1551 – 2300 MHz	≤ 4.8	≤ 2.2	≤ 2.2
Directional isolation	5 – 300 MHz	≥ 30	≥ 30	≥ 33
	301 – 862 MHz	≥ 30	≥ 30	≥ 36
	950 – 2300 MHz	≥ 27	≥ 23	≥ 28
Tap-to-tap isolation	5 – 300 MHz	≥ 34	≥ 30	≥ 30
	301 – 862 MHz	≥ 32	≥ 28	≥ 28
	950 – 2300 MHz	≥ 25	≥ 28	≥ 28
Return loss	dB		≥ 10 (TV) ≥ 10 (SAT)	
Dimensions	mm		120 x 60 x 20	