



Masts and supports



SCF-085



MAS-300



MAS-250



TOR-250



TOR-150



KMV-100



GME-200




BBT-100



BAP-200



BFT-100



BTA-225



GMA-400



SPA-240



BMA-200

MODEL	REF.	DESCRIPTION
SCF-085	1067	Ground-fixing "column" type. Heigh 90cm. Pipe of Ø50mm. Base 200x200 mm
MAS-300	1941	Plug-in mast 3m length x 40mm Ø. Thickness 2 mm
MAS-250	1880	Plug-in mast 2.5m length x 35mm Ø. Thickness 1,5 mm
TOR-250	1942	Trestle-power 2.5m. Top end adapted for housing the point mast
TOR-150	1944	Trestle-power 1.5m. Top end adapted for housing the point mast
BFT-100	1876	Hooked, triangular fixed base side 225mm. Three bolts for securing
BTA-225	1950	Screwed, triangular fixed base side 225mm. Three bolts for securing
KMV-100	1888	Wind set. Steelwire 25m, rigging screw, wirelock, for Ø 30-35 mm masts
GME-200	1886	Wall support bracket for Ø ≤45 mm masts
BBT-100	1913	Titable ridge-tale base for Ø30 to 35 mm masts
BAP-200	1949	Hooked-support for SCF-085. Plate 200x200x2 mm and four M12 treaded hooks
GMA-400	1911	Wall-screwing clamp, length 40 cm for Ø ≤45 mm masts
SPA-240	3071	Wall-fixing "U" type. Wind of the arm: 24 cm. Pipe of Ø40 mm made of galvanized steel
BMA-200	1887	Single angle pipe with 4 screws plate and polythene cap